Mumble Client How-To

This is the 5th dialog box you will see after starting the Mumble client for the first time. Accept the defaults on the first four dialogs. In this dialog select "Push To Talk" and press the keyboard combination you prefer to use when you want to speak. I use "Control + z".

Ŧ	Audio Tuning Wizard	×
Voice Activity Detect Letting Mumble fig	tion jure out when you're talking and when you're silent.	
This will help Mum	ble figure out when you are talking. The first step is selecting which data value to use.	
O Push To Talk:	Control_L + z	
Raw amplitude	e from input	•
Signal-To-Nois	e ratio	
Next you pood to a	adjust the following slider. The first few utterances you say should end up in the green area	
(definitive speech)	. While talking, you should stay inside the yellow (might be speech) and when you're not talking,	
everytning should	be in the red (definitively not speech).	
	w=	
	< <u>Back</u> <u>N</u> ext > Cancel	

The next dialog you need to select "Disable Text-To-Speech and use sounds instead. Accept the defaults for the remaining dialogs until the wizard is finished.

-	Audio Tuning Wizard	×
Quality & Notificati Adjust quality and	ions d notification settings.	
Quality settings		
○ Low	In this configuration Mumble will use a low amount of bandwidth . This will inevitably result in high latency and poor quality. Choose this only if your connection cannot handle the other settings. (Speex 16kbit/s, 60ms per packet)	
O Balanced	This is the recommended default configuration. It provides a good balance between quality, latency, and bandwidth usage. (CELT 40kbit/s, 20ms per packet)	
🔿 High	This configuration is only recommended for use in setups where bandwidth is not an issue, like a LAN. It provides the lowest latency supported by Mumble and high quality . (CELT 72kbit/s, 10ms per packet)	
Notification sett	ings	
🔘 Use Text-	To-Speech to read notifications and messages to you.	
Disable Te	ext-To-Speech and use sounds instead.	
🔘 Keep cus	tom Text-To-Speech settings.	
	< <u>B</u> ack <u>N</u> ext > Cancel	

Next, select the "Server" drop-down menu and then select "Connect". Next click on "Add New...".

-	Mumble 1.2.3-2+b2				
<u>erver</u>	Self Configure Help Mumble Server Connect			×	1
	Mulliple Server connect			<u></u>	
	Servername	Ping V	Users	Â	-
1:13 Pl	🖃 🚷 Public Internet				
	🛨 🌏 Africa			U	
	🛨 🌏 Asia				
	🛨 🌏 Europe				
	🖃 🔕 North America				
	🛨 🕒 Canada				
	🖃 🌉 United States				
	Communist Land	24	2/15		
	Prestigious	25			
	Too Deep	22	4/25		
	[USA] Gaming Community Public	23	104/500		
	GeekedGamer.com Free Mumble 1.2.3 [250 slots] -	Chicago 24	17/250		
	HackThisSite	24			
	RebellionHQ	26	4/1000		
	Lead and Sails PTT and 16 or Older	27	2/30		
	ESEA.net Public Mumble Server #3	25	2/50		
	AddMan	Creat			
	Add New	Cancel	Conne		
					2
	Not connected				

In the Add Server dialog you will need to add a Label name of your choice, the server IP "174.123.227.204", Port number 43556, and then a user name of your choosing. This will be how you will be shown in the Mumble server. Select "OK" to save and close this dialog.

-	Add Server ×
Label	HPR
A <u>d</u> dress	174.123.227.204
<u>P</u> ort	43556
<u>U</u> sername	KevinW
	<u>Cancel</u> <u>OK</u>

You will now see the new server show up in the Mumble Server Connect window. Make sure the new server entry is selected and then click on the "Connect" button.

•	Mumble Serv	ver Connect			,
Servername			Ping	v	Users
🖃 🖤 Favorite					
HPR					
🖃 🌏 Public Internet					
🛨 🌏 Africa					
🛨 🌏 Asia					
🕂 🌏 Europe					
🛨 🌏 North America					
🛨 🌏 Oceania					
玊 🌏 South America					
		Add New	<u>C</u> ancel		<u>C</u> onnect
+ 🌏 Europe + 🌏 North America + 🌏 Oceania		<u>A</u> dd New	Cancel		Connect

You will now see Mumble security certificate dialog. Select "Yes" to accept.



You will now need to input the sever password, OSMPMumble

-	Wrong password ×
W	rong server password for unregistered user account, please try again.
	<u>Cancel</u> <u>OK</u>

You should now be connected to the server. The next step is to select the "Configure" drop-down menu and make sure to clear the check mark on "Text-To-Speech" if you happened to miss this selection during the setup wizard.

Mumble 1.2.3-2+b2	- + ×
Server Self Configure Help	
Image: Settings Audio Wizard Certificate Wizard	
11:13 PM] Wel Set Circle With a G 11:48 PM] SSL Inimal View 11:51 PM] Reconnecting. Ificate is self-signed, and untrusted 11:51 PM] Connected. Isin PM] Server connection rejected: Invalid server password. 11:54 PM] Reconnecting. Isin PM] Reconnecting. 11:54 PM] Welcome message: Isin PM] Reconnecting. Welcome to OSMP Server Murmur. Enjoy your stay!	OSMP Mumble Book Club Chit Chat Annoyance asteriskMeetme Azimuth ClaudioM DoorToDoorGeek FiftyOneFifty Frank
[1:54 PM] Disconnected from server. [1:56 PM] Connecting to server 174.123.227.204. [1:56 PM] Connected. [1:56 PM] Welcome message: Welcome to OSMP Server Murmur . Enjoy your stay!	jneusteter ken_fallon KevinW klaatu Krayon neoteny pegwole
[1:57 PM] UDP packets cannot be received from the server. Switching to TCP mode. [1:57 PM] Frank entered channel. [1:57 PM] Frank moved to Chit Chat.	 phil PipeManMusicStudio pokey_HPR pokey_recording corenominal KWisher
Type message to channel 'OSMP Mumble' here	

The last step is to select the "Configure" drop-down menu and then select "Settings". The dialog window below will be shown. You will need to slide the "Compression" slider to the left until it is around 31.0 kb/s and the Speex codec is being used. Select "Apply" and you are now ready to start using Mumble.

		Mumble	Configuratio	n		
Audio Input	Transmission Transmit		Push To Talk			v]
Shortcuts Network Overlay	Compression Quality	45.8 kbit/s	(Audio 31.0 Speex,	Position 0.0, Overh	ead 14.8)	- 31.0 kb/s